



HD-SDI 1080P

UH-VVHD8TD



Full HD
1920x1080

FEATURES

- 1/2.9" SONY CMOS (2.1 Mega Pixel)
- HD-SDI (1080p@25/30fps) video output
- Verifocal Lens 2.8~12mm
- WDR, 3D-DNR
- Day&Night function (ICR)
- OSD, Sens-Up
- RS-485 Interface
- Vandal-proof & Waterproof(IP68)
- LED 24pcs(0Lux 25M Range, Indoor)
- Dual Voltage(12V DC, 24V AC)
- Wall & ceiling mountable

SPECIFICATIONS

UH-VVHF8TD

VIDEO	Image Sensor	1/2.9" SONY CMOS	
	Effective Pixel	1984(H)x1105(V)	
	Scanning System	Progressive Scan	
	Resolution	Digital: 1080p (1920x1080)	
	Video Output	HD-SDI (1080p@25/30fps)	
	Min. Illumination	Color: 1.0Lux, BW: 0.5Lux	
	LED	24pcs. Smart IR (60FT Range)	
	Focal Length	f = 2.8(W) ~ 12.0(T)mm	
	OPERATION	Day & Night	ICR (Auto, Color, B/W)
		Backlight Compensation	BLC / HLC / WDR / OFF
Digital Noise Reduction (3D)		High / Middle / Low / Off	
Digital Zoom		ON/OFF (x1 ~ x8)	
Defog, DWDR		OFF / LOW/ MIDDLE / HIGH	
Motion Detection		ON/OFF	
Privacy Masking		ON/OFF (16 Zone Selectable)	
Sense-up		Auto (Selectable limit 2x ~ 32x)/OFF	
ENVIRONMENT	White Balance	Auto / Autoext / Manual	
	Ingress Protection	IP 68	
	Operating Temp.	-45C ~ 50C	
FUNCTION	Humidity	0% to 90%	
	Protocol	PELCO D	
ELECTRICAL (Power Supply)	Communication	RS-485	
	Supplied Voltage	Max 1A(at 12v DC, 24V AC) : LED ON	
	Power Consumption	Max 600mA(at 12v DC) : LED ON	
MECHANICAL	Heater	Yes	
	Dimension	Ø150.5 x 95.6(H) mm	
	Weight	Approx. 1kg	
	CE, FCC, ROHS	Yes	

DIMENSIONS

