



## FEATURES

- 2.1 Mega Pixel, 1/3" Exmor SONY CMOS
- 1080p(1920x1080)@30fps (Standard)
- Board Lens
- Digital Day & Night
- WDR, 3DNR, BLC, AGC
- Privacy Masking, Motion Detection
- Convenient OSD
- HD-SDI (BNC) / Service Video Output



## UH-DFHD0S

### 2.1 Mega Pixel Flat Plastic Dome Camera

## SPECIFICATIONS

Image Device	2.1 Mega Pixel, 1/3" Exmor SONY CMOS	
Video Output Mode	HD-SDI : 1080p@30fps, 1080p@25fps, 720p@60fps, 720p@50fps TV Out : NTSC / PAL Selectable	
Effective Pixels	1984(H) x 1105(V)	
Unit cell size (um)	2.8(H) x 2.8(V)	
S/N Ratio	More than 50 dB	
Min. Illumination	0.1 Lux	
Video output	HD-SDI / 1.0 Vp-p Composite (75Ω)	
Lens	Board Lens	
Shutter Speed	Auto / Manual Selectable	
Flickerless	60Hz / 50Hz Selectable	
WDR / BLC	OFF / WDR / BLC Selectable	
AGC	0~23 dB	
3DNR	OFF / LOW / MIDDLE / HIGH	
White Balance	AUTO / PUSH LOCK / MANUAL	
Digital Zoom Ratio	1x ~ 20x	
Digital Slow Shutter	Off, x2, x3, x4	
Privacy Masking	Zone 30, On / Off	
Motion Detection	On / Off	
Day & Night	Digital Day & Night	
OSD	Built-in	
Operating Temperature	14°F~122°F (-10°C~+50°C)	
Storage Temperature	-4°F~140°F (-20°C~+60°C)	
Humidity	Operating: Less than 80% / Storage: Less than 95%	
Power Consumption	DC12V	DC12V (±10%), Max. 150 mA
	Dual	DC12V (±10%), Max. 200 mA / AC24V (±10%), Max. 2.5 W
Dimension (mm)	119(W) x 42(H) x 119(D)	
Weight	Approx. 200 g	

## DIMENSIONS

