



FEATURES

- 2.1 Mega Pixel, 1/3" Exmor SONY CMOS
- 1080p(1920x1080)@30fps (Standard)
- WDR, BLC, AGC, 3DNR
- Weatherproof & Vandal-Resistant (IP66)
- Privacy Masking, Motion Detection
- Convenient OSD
- Digital Day & Night



UK-VFHD0S-K

High Definition Low Profile Vandal-Resistant Dome



SPECIFICATIONS

Image Sensor	2.1 Mega Pixel, 1/3" Exmor SONY CMOS K
Video output	HD-SDI / 1.0 Vp-p Composite (75Ω)
Active Pixels	1984(H) x 1105(V)
S/N	More than 50dB (AGC OFF)
Video Output Mode	HD-SDI : 1080p@30fps, 1080p@25fps, 720p@60fps, 720p@50fps TV Out : NTSC / PAL
3DNR	OFF / LOW / MIDDLE / HIGH
Min. Illumination	0.1 Lux
Day & Night	Electronic(AUTO, COLOR, B/W)
White Balance	AUTO / PUSH LOCK / MANUAL
Digital Slow Shutter	Off, x2, x3, x4
Motion Detection	ON/OFF (64 Zone)
Shutter Speed	Auto / Manual Selectable
Privacy Zone	Zone 30, On / Off
Backlight	BLC/HLC/OFF
AGC	LOW/MIDDLE/HIGH/OFF
WDR	D-WDR
Lens	3.6 Fixed
OSD	Built-in
Operating Temp	14°F~122°F (-10°C~+50°C)
Current Consumption	DC12V : DC12V (±10%), Max. 150 mA Dual : DC12V (±10%), Max. 200 mA / AC24V (±10%), Max. 2.5 W
Dimension (mm)	139(W) x 49(H) x 134(D)
Weight	Approx. 500 g

• Dimensions

(Unit : mm)

