



## FEATURES

- This camera is incredibly flexible to install with its 3-axis camera construction, which makes the camera ceiling, wall or slope mountable.
- 25M range visible in total darkness with 24pcs of IR LEDs.
- Mechanical filter exchange(True Day & Night), built-in WDR function.
- Supreme Resolution.(690 TV-Line)



## UK-D28VP8TWD 3-AXIS WDR SUPREME RESOLUTION DAY & NIGHT IR DOME CAMERA

### SPECIFICATIONS

Image Sensor	1/3" PIXIM DPS SENSOR - SEAWOLF
Effective Pixel	758(H) X 540(V) PIXEL
Resolution	690 TV- Line
TV Type	NTSC / PAL
Sync. Type	Internal
Scanning System	Progressive scan
Video Output	1.0 Vp-p(Sync. Negative) Termination 75Ω±10%
Gamma Characteristic	γ= 0.45(Selectable)
White Balance	ATW / AWC / MANUAL(2,000 ~ 11,000 )
Min. Illumination	Color: F1.2 0.01 LUX B/W: 0.0001 LUX (Sens-Up X64), 0LUX (IR on)
S/N Ratio	More 50 dB(AGC OFF)
SDNR	ON
Backlight	WDR / BLC / OFF
Day & Night	True D&N(AUTO / COLOR / BW)
Gain Control	AUTO / MANUAL
Sense Up	Max. X64(X2, X4, X8, X16, X32, 64)
Test Illumination	Average test illuminance by front view
Power Supply	Regulated 12V DC or 24V AC
Current Consumption	Max. 500mA(at 12V DC)/LED ON, Max. 510mA(at 24V AC)/LED ON
Reverse Polarity Protection	Yes
Lens	Vari focal auto iris lens 2.8 ~ 12mm
Operation Temp.	-10 ~ 50°C
Preservation Temp.	-20 ~ 60°C
Dimension	Ø130.8 X 96(H)mm
Weight	Approx. 500g

### DIMENSIONS

