



Unitek

FEATURES

- IP67(Waterproof)
- Durable MATERIAL : Body - Aluminum, Dome - Polycarbonate
- This camera is incredibly flexible to install with its 3-axis camera construction, which makes the camera ceiling, wall or slope mountable.
- 25M range visible in total darkness with 24pcs of IR LEDs.
- Mechanical filter exchange(True Day & Night), built-in WDR function.
- Adopted DNR technology, It reduces noise efficiently in low light condition.
- SupremeResolution.(690 TV-Line)
- Multi-language full OSD support.



UK-V28VP8TWD

VANDAL-PROOF & WATERPROOF WDR IR D&N 3-AXIS DOME CAMERA

SPECIFICATIONS

Image Sensor	1/3" PIXIM DPS SENSOR - SEAWOLF	
Effective Pixel	758(H) X 540(V) PIXEL	
Resolution	690 TV- Line	
TV Type	NTSC / PAL	
Sync. Type	Internal	Internal / External
Scanning System	Progressive scan	
Video Output	1.0 Vp-p(Sync. Negative) Termination 75Ω±10%	
Gamma Characteristic	γ= 0.45(Selectable)	
White Balance	ATW / AWC / MANUAL(2,000 ~ 11,000)	
Min. Illumination	Color: F1.2 0.1 LUX B/W: 0.0001 LUX (Sens-Up X64), 0LUX (IR on)	
S/N Ratio	More 50 dB(AGC OFF)	
SDNR	ON	
Backlight	WDR / BLC / OFF	
Day & Night	True D&N(AUTO / COLOR / BW)	
LED Output	Level adjustable	
Gain Control	AUTO / MANUAL	
Sense Up	Max. X64(X2, X4, X8, X16, X32, 64)	
Test Illumination	Average test illuminance by front view	
Power Supply	Regulated 12V DC or 24V AC	
Current Consumption	Max. 500mA(at 12V DC)/LED ON, Max. 510mA(at 24V AC)/LED ON	
Reverse Polarity Protection	Yes	
Lens	Vari focal auto iris lens 2.8 ~ 12mm	
Operation Temp.	-10 ~ 50°C	
Preservation Temp.	-20 ~ 60°C	
Dimension	Ø150.5 X 95.6(H)mm	
Weight	Approx. 800g	

DIMENSIONS

